

Guide for Stripper Bolts

Male Screw Stripper Bolts		Bushing Stripper Bolts		Stroke Extension Retainers for Stripper Bolt	
MMSB	P.875	SSBWH	P.876	MMSBE	P.877
MMSBL	P.876				
	In stock				

Bushing Stripper Bolts		Female Screw Stripper Bolts		Female Screw Stripper Bolts L Dimension Designated Type	
SSBTH	P.878	SSBT	P.880	SSBTL	P.881
SSBRH		SSBTN		SSBTLN	
SSBJH		SSBTC		SSBTK	
SSB		SSBTCN		SSBTKN	
			In stock		

Pressure Pins for Stripper		Pressure Pins for Stripper		Pressure Pins for Stripper	
HHSP	P.882	PPWP	P.882	SSBKP	P.883
HHSPPH					

Pressure Pins for Stripper		Hang Collars for Stripper		Hang Collars for Stripper	
SSBKS	P.883	SSBKT	P.883	SSBK	P.883

Male Screw Stripper Bolts

RoHS

Material	Hardness	Code
SCM435	33~38HRC	MMSB

Surface treatment: Blacking (Fe₃O₄)
 ▲ Strength class 10.9

De9	A	B	C	E	F	MxP	T
4	6.5					2.5X0.45	4.5
4.5	7	2.5	1.6	3	5		5
5	8			3.5	6	3 X0.5	5.5
5.5							6
6	9	3	2.2	4	7	4 X0.7	6.5
6.5	10	4	2.5	5	9	5 X0.8	7
8	13	5	3	6	9	6 X1.0	8.7
10	16	6	4	8	12	8 X1.25	10.8
12	17						12.8
13	18	8	5	10	16	10 X1.5	14
16	24	10	7	14	18	12 X1.75	17
20	27	14	9	18	24	16 X2.0	21

ORDER Code No. MMSB4 - 15 DELIVERY In stock working day P.38

PRICE Quantity discount rate P.38 (Prices less than 1¥ are rounded off)

Quantity	Discount Rate
1~19	100%
20~49	95%
50~199	90%
200~500	85%
501~	Enquiry

Code No.	D	L															@/P (1~19P)			
MMSB	4	15	20	25	30	35	40												58	
		10						45											75	
	4.5	15	20	25	30	35	40												58	
		10						45	50										75	
	5	15	20	25	30	35	40												65	
		10						45	50										80	
	5.5	15	20	25	30	35	40												58	
		10						45	50	55									75	
	6	15	20	25	30	35	40												80	
		10						45	50	55	60	65	70						100	
	6.5	15	20	25	30	35	40												58	
		10						45	50	55	60	65	70	75	80				70	
	8	15	20	25	30	35	40	45											70	
		10						50	55	60	65	70	75	80	85	90			85	
	10	15	20	25	30	35	40	45	50	55						95	100	110	120	113
		10						60	65	70	75									90
	12	15	20	25	30	35	40	45	50	55										108
		10						60	65	70	75					80	85	90	95	100
	13	15	20	25	30	35	40	45	50	55	60	65	70							123
		10						75	80	85	90	95	100							148
16	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85				128	
	10						110	120	130										168	
20	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85				223	
	10						90	95	100										233	
	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85				248	
	10						110	120	130	140	150								333	
	10						110	120	130	140	150								353	
	10						110	120	130	140	150								438	

MMSRB (spacers for male screw stripper bolt)

RoHS

Material	Code
SK85	MMSRB

Code No.	d	t	D	@/P			
MMSRB	*4		6.5	1~49P	50~99P	100~499P	500~1000P
	4.5		7	12	10	6	6
	*5		8	12	10	6	6
	5.5	0.1	9	12	10	6	6
	*6	0.2	9	12	10	6	6
	6.5	0.3	10	12	10	6	6
	8	0.5	13	13	12	8	8
	10	1.0	16	15	14	10	9
	*12	2.0	17	19	17	12	11
	13		18	19	17	12	11
	16		24	22	20	15	14
	20		27	28	26	21	20

ADD

Add.	Code (@/P)	Spec.
L dimension alteration	LC	Lmin ≤ LC ≤ Lmax ① 0.1 ▲ F dimension is according to the standard table. For F dimension alteration, combine with FC. ▲ Cancel the surface treatment on thread part. ▲ LC dimension tolerance is ±0.05.
Thread part length alteration	FC (FC < F → -0) (FC > F → +60)	M ≤ FC ≤ M × 3 ① 0.5 ▲ For D = 4, 3 ≤ FC ≤ 7.5 ▲ Combined with LC is available only.

ORDER Code No. MMSB4 - LC17.5 - FC3 DELIVERY In stock working day P.38

PRICE Product unit price + Addition unit price. Price discount is also available for addition. P.36

Stripper Bolts